

KASTREDSKAPENS GRUNDMÅTT 2009

(inga ändringar från år 2008)

Klass	Minimi vikt /g	Tillverkn. gränser / g	Diameter /mm	Tjocklek /mm	Mittskivans diam. /mm	Släggans längd fr. handt. inre kant/mm
-------	----------------	------------------------	--------------	--------------	-----------------------	--

KULA

H	7260	7265-7285	110-130			
H22	7260	7265-7285	110-130			
H19	6000	6005-6025	105-125			
H17	5000	5005-5025	100-120			
P15	4000	4005-4025	95-110			
P14	4000	4005-4025	95-110			
P13	3000	3005-3025	90-100			
P12	3000	3005-3025	90-100			
P11	2500	2505-2525	85-95			
P10	2500	2505-2525	85-95			
P9	2000	2005-2025	80-90			
D	4000	4005-4025	95-110			
D22	4000	4005-4025	95-110			
D19	4000	4005-4025	95-110			
D17	3000	3005-3025	90-100			
F15	3000	3005-3025	90-100			
F14	3000	3005-3025	90-100			
F13	2500	2505-2525	85-95			
F12	2500	2505-2525	85-95			
F11	2000	2005-2025	80-90			
F10	2000	2005-2025	80-90			
F9	2000	2005-2025	80-90			

DISKUS

H	2000	2005-2025	219-221	44-46	50-57
H22	2000	2005-2025	219-221	44-46	50-57
H19	1750	1755-1775	210-212	41-43	50-57
H17	1500	1505-1525	200-202	38-40	50-57
P15	1000	1005-1025	180-182	37-39	50-57
P14	1000	1005-1025	180-182	37-39	50-57
P13	600	605-625	(155-161)	(28-35)	(37-45)
P12	600	605-625	(155-161)	(28-35)	(37-45)
P11	600	605-625	(155-161)	(28-35)	(37-45)
P10	600	605-625	(155-161)	(28-35)	(37-45)
P9	-	-	-	-	-
D	1000	1005-1025	180-182	37-39	50-57
D22	1000	1005-1025	180-182	37-39	50-57
D19	1000	1005-1025	180-182	37-39	50-57
D17	1000	1005-1025	180-182	37-39	50-57
F15	750	755-775	(165-172)	(33-37)	(45-55)
F14	750	755-775	(165-172)	(33-37)	(45-55)
F13	600	605-625	(155-161)	(28-35)	(37-45)
F12	600	605-625	(155-161)	(28-35)	(37-45)
F11	600	605-625	(155-161)	(28-35)	(37-45)
F10	600	605-625	(155-161)	(28-35)	(37-45)
F9	-	-	-	-	-

Klass	Minimi vikt / g	Tillverkares gränser / g	Diameter /mm	Tjocklek /mm	Mittskivans diam. /mm	Släggans längd fr. handt. inre kant/mm
-------	-----------------	--------------------------	--------------	--------------	-----------------------	--

SLÄGGA

H	7260	7265-7285	110-130			1175-1215
H22	7260	7265-7285	110-130			1175-1215
H19	6000	6005-6025	105-125			1175-1215
H17	5000	5005-5025	100-120			1165-1200
P15	4000	4005-4025	95-110			1160-1195
P14	4000	4005-4025	95-110			1160-1195
P13	3000	3005-3025	90-100			1160-1195
P12	3000	3005-3025	90-100			1160-1195
P11	-	-	-			-
P10	-	-	-			-
P9	-	-	-			-
D	4000	4005-4025	95-110			1160-1195
D22	4000	4005-4025	95-110			1160-1195
D19	4000	4005-4025	95-110			1160-1195
D17	4000	4005-4025	95-110			1160-1195
F15	3000	3005-3025	90-100			1160-1195
F14	3000	3005-3025	90-100			1160-1195
F13	2500	2505-2525	85-95			950-990
F12	2500	2505-2525	85-95			950-990
F11	-	-	-			-
F10	-	-	-			-
F9	-	-	-			-

SPJUT

			Största diam./mm	Längd /cm	Spetsens avst till tyngdp./cm	Handtagets längd / mm
H	800	805-825	25-30	260-270	90-106	150-160
H22	800	805-825	25-30	260-270	90-106	150-160
H19	800	805-825	25-30	260-270	90-106	150-160
H17	700	705-725	23-28	230-240	86-100	150-160
P15	600	605-625	20-25	220-230	80-92	140-150
P14	600	605-625	20-25	220-230	80-92	140-150
P13	400	405-425	17-23	185-205	handtag	125-145
P12	400	405-425	17-23	185-205	handtag	125-145
P11	400	405-425	17-23	185-205	handtag	125-145
P10	400	405-425	17-23	185-205	handtag	125-145
P9	350 g	("juniorspjut")				
D	600	605-625	20-25	220-230	80-92	140-150
D22	600	605-625	20-25	220-230	80-92	140-150
D19	600	605-625	20-25	220-230	80-92	140-150
D17	600	605-625	20-25	220-230	80-92	140-150
F15	400	405-425	17-23	185-205	handtag	125-145
F14	400	405-425	17-23	185-205	handtag	125-145
F13	400	405-425	17-23	185-205	handtag	125-145
F12	400	405-425	17-23	185-205	handtag	125-145
F11	400	405-425	17-23	185-205	handtag	125-145
F10	400	405-425	17-23	185-205	handtag	125-145
F9	350 g	("juniorspjut")				